


CM-4020



Features :

- Data Hold
- True RMS
- Multi-Functions
- Electrical Repair
- Appliance Repair
- Home wiring projects
- Testing electrical systems on cars and boats
- Solar Panel Testing



Technical Data

SPECIFICATION	RANGE	ACCURACY
MEASUREMENT		CM-4020
DC Voltage	2V/20V/200V/2000V	±(0.5%+5)
AC Voltage	2V/20V/200V/2000V	±(0.8%+5)
DC Current	20A/200A/2000A	±(1.9%+10)
AC Current	20A/200A/2000A	±(1.9%+10)
Resistance	200Ω /2kΩ /20kΩ / 200kΩ /2MΩ / 20MΩ	±(0.8%+5)
Capacitance	20nF/200nF/2uF/200uF	±(3%+10)
FEATURES		
Display	Count	1999
Sampling Rate	2.5 times/s	3
Operating Method	Auto/Manual/Range	3
Jaw Opening	55 MM	3
Continuity Buzzer	Less than about 50Ω	3
Diode		3
Data Hold		3
Inrush Current		3
Clamp Light		3
Back Light		3
Auto Power Off		3
Function Protection		3
GENERAL		
Power Supply	9V (6F22 Battery)	
Product Size	270x100x46mm	
Product Weight	About 460g (Including Battery)	
Standard Accessory	Test Leads, Battery, Manual, Carry Case	

HATCO IS BRAND COMPANY OF HTC INSTRUMENT

